

# Monofil - Mono-Spray Premium Clear Lacquer

## Product Information

Monofil Mono-spray 1K Clear Lacquer acrylic spray is a fast drying weather and light resistant protective coating for the clear over base coating of metallic base-coats  
The clear lacquer provides a tough long lasting protective coating and also protects the paint from the drop of gloss.



### Properties:

It sprays to give a tough acrylic finish.  
It is advised to spray a sample first!




### Pre-treatment / Cleansing:

Pre-cleansing with a good Panel Wipe

---

### Coating Procedure



### Process:

Please read the directions for use!

### Characteristics

Fast drying,  
Weather Resistant  
Good adhesion.

### Colour

Clear

### Processing Conditions

from +10°C and up to 80% relative air humidity.

---

### Drying Times:

Set to touch  
Full hardness



after approx. 20—30 mins at 20° C.  
after 24 hours at 20° C.

---

### Directions for use:

Allow the previous metallic base-coat to dry for approx. 30 minutes. Shake the can vigorously for approx. 3 mins. prior to use and spray several light coats from 25 – 30cm, allowing a 10-15 min. flash off time in between coats. After use, invert can and spray for a few seconds to clear the nozzle. This prevents the aerosol from clogging up when using next time

### Safety Information:

Only to be used in well ventilated areas. Keep away from sources of ignition, do not smoke, eat or drink. Keep out of the reach of children. **Caution!** Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. For professional use only. **Caution!** Disposal only in accordance to the regulations of the environmental health authorities.

The data sheet is for information purposes only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.