

Relofix

PE-Glasfaserspachtel Product-Information

GB 1/0413

Page 1 / 1

Relofix is a 2-component glass fibre putty based on polyester resins free of asbestos. Because of its content of glass fibre splinters the product is especially suited for bridging cracks, small holes and rusted-through areas on iron, steel and glass fibre. As the product contains no soluble compounds and does not wash out, it is ideal for all marine repairs. An application on vertical surfaces is possible without problems.

milky yellow				
100 : 2				
Härter P				
spraying pressure		spraying nozzle		spraying operations
4 - 5 min.				
recoat time	dust dry		set to touc	h full hardness
Sandable after approx. 20 min.				
Sandable after approx. 10 min.				
EC limiting value for the product (cat. B/b): 250 g/l (2007) This product contains max. 0 g/l VOC [0 lbs/gal]				
	100 : 2 Härter P spraying press 4 - 5 min. recoat time Sandable afte Sandable afte EC limiting val	100 : 2 Härter P spraying pressure 4 - 5 min. recoat time du Sandable after appr Sandable after appr EC limiting value for	100 : 2 Härter P spraying pressure spraying 4 - 5 min. recoat time dust dry Sandable after approx. 20 m Sandable after approx. 10 m EC limiting value for the processor.	Härter P spraying pressure spraying nozzle 4 - 5 min. recoat time dust dry set to touc Sandable after approx. 20 min. Sandable after approx. 10 min. EC limiting value for the product (cat. B/l

Application conditions:

Apply over +10° C and at max. 80% relative air humidity.

Remarks

The substrate must be clean, dry and free of grease. Slightly sand surfaces! Remove old layers of paint or primer, which are not adhesive or fully dry. Do not apply on thermoplastic or acid-containing coats (eg. Washprimer). Mix well Relofix and Härter P.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your environment.

This data sheet is for information purpose only! To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty. Please follow recommendations stated on the relevant safety data sheet and precautions stated on the product label. We reserve our right to make additions, deletions, or modifications to the information at any time without prior notification.