



Mono-Spray Xtreme Performance Range

Xtreme Multi Functional Adhesion Aid

Product Information

Designed specifically to bond to difficult, non-porous or non-ferrous substrates and to provide a surface suitable for the subsequent application of primers, finishes and lacquers.



Where to use:

On rigid non-porous plastics, including melamine and phenol formaldehydes, rigid (unplasticised) PVC, ABS, laminates and galvanised and non-ferrous metals.


Where not to use:

Very flexible plastics, Thermoplastics such as acrylics, polystyrene, polycarbonates polyolefins etc.

Pretreatment / Cleansing:

Pre-cleansing with a good panel wipe

Process: Coating Procedure



Please read the directions for use!

Characteristics

Promotes optimum adhesion to problematic substrates
Eliminates the need for specialist pre-treatments

Colour

Clear

Processing Conditions

from +10°C and up to 80% relative air humidity.

VOC-regulation EC limiting value for the product (cat. B/e): 840 g/l (2007)
This product contains max. 725 g/l VOC

Drying Times:



Re-coatable

after at least 30 min

Directions for use:

Prepare the area to be treated, ensuring freedom from dust, grime, greases, oils etc. using panel wipe. Corrosion, other surface contamination and loose adhering matter should be removed with an appropriate grade of wet and dry abrasive paper.

Shake can thoroughly before use. Repeat shaking at regular intervals during use.

Apply sparingly from a distance of 20-25cm. Apply two light coats and leave for at least 30 mins prior to the application of a primer or finishing coat.

After use, turn can upside down and spray for a few seconds to clear the nozzle. This prevents the valve from clogging up when using next time.

Safety Information: Read the corresponding Material safety data Sheet

Only to be used in well ventilated areas. Keep away from sources of ignition, do not smoke, eat or drink.

Keep out of the reach of children. **Caution!** Pressurised container.

Protect from sunlight and do not expose to temperatures exceeding 50°C.

For professional use only. **Caution!** Disposal only in accordance to the regulations of the environmental health authorities.

The data sheet is for information purposes only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.

MONOFIL – Applied House, Fulflood Road, Havant, Hampshire. PO9 5AX

Tel: +44 (0) 239 2470909 - Fax: +44 (0) 239 2476340

Internet: www.monofil.co.uk e-mail: sales@monofil.co.uk