



# Mono-Spray Xtreme Performance Range

## Xtreme Alu Wheel Silver Aerosol

### Product Information

An acrylic fast drying spray, with good protection against weathering and yellowing for wheel rims and other vehicle parts.

Sprays to give a tough durable acrylic coating. It is recommended to use the Xtreme etch primer spray in order to improve the adhesion and corrosion protection of the wheel rims



#### Properties:


It sprays to give a tough acrylic finish  
It is advised to spray a sample first!



#### Pretreatment / Cleansing:

Pre-cleansing with a good panel wipe

#### Process: Coating Procedure



Please read the directions for use!

#### Characteristics

Fast drying.  
Weather resistant.  
Good adhesion

#### Colour

Silver

#### Processing Conditions

from +10°C and up to 80% relative air humidity.

VOC-regulation EC limiting value for the product (cat. B/e): 840 g/l (2007)  
This product contains max. 638 g/l VOC

#### Drying Times:

##### Set to touch Full Hardness



after approx. 20—30 minutes at 20° C.  
after approx. 24 hours at 20° C

#### Directions for use:

Ensure surface to be sprayed is clean and free from any traces of corrosion, grease, oil or polishing agent. Lightly abrade the surface. Shake can vigorously for approx. 3 mins. prior to use and spray several light coats from a distance of 20 -30 cm. allowing a 10 min. flash off time in between coats

After use, turn can upside down and spray for a few seconds to clear the nozzle. This prevents the valve from clogging up when using next time.

#### Safety Information:

Only to be used in well ventilated areas. Keep away from sources of ignition, do not smoke, eat or drink. Keep out of the reach of children. **Caution!** Pressurised container.

Protect from sunlight and do not expose to temperatures exceeding 50°C.

For professional use only. **Caution!** Disposal only in accordance to the regulations of the environmental health authorities.

The data sheet is for information purposes only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.

MONOFIL – Applied House, Fulflood Road, Havant, Hampshire. PO9 5AX

Tel: +44 (0) 239 2470909 - Fax: +44 (0) 239 2476340

Internet: [www.monofil.co.uk](http://www.monofil.co.uk) e-mail: [sales@monofil.co.uk](mailto:sales@monofil.co.uk)